

CQB-G 型不锈钢高温磁力泵性能参数表

型号	口径 (mm)		流量 (m ³ /h)	扬程 (m)	汽蚀余量 (m)	电机功率 (kW)	转速 (r/min)	电压 (V)
	进口	出口						
CQB32-20-125G	32	20	3.2	20	4.5	1.5	2900	380
CQB32-20-160G				32	4.5	2.2	2900	380
CQB40-25-125G	40	25	6.3	20	4.5	2.2	2900	380
CQB40-25-160G				32	4.5	3	2900	380
CQB40-25-200G				50	4.5	5.5	2900	380
CQB50-32-125G	50	32	12.5	20	4.0	3	2900	380
CQB50-32-160G				32	4.0	4	2900	380
CQB50-32-200G				50	4.0	7.5	2900	380
CQB50-32-250G				80	4.0	15	2900	380
CQB65-50-125G	65	50	25	20	4.0	5.5	2900	380
CQB65-50-160G				32	4.0	7.5	2900	380
CQB65-40-200G	65	40	25	50	4.0	15	2900	380
CQB65-40-250G				80	4.0	22	2900	380
CQB80-65-125G	80	65	50	20	3.5	7.5	2900	380
CQB80-65-160G				32	3.5	15	2900	380
CQB80-50-200G	80	50	50	50	3.5	22	2900	380
CQB80-50-250G				80	3.5	37	2900	380
CQB100-80-125G	100	80	100	20	3.2	15	2900	380
CQB100-80-160G				32	3.2	22	2900	380
CQB100-65-200G	100	65	100	50	3.2	37	2900	380
CQB100-65-250G				80	3.2	55	2900	380